

WO 2004/016796

PCT/SE2003/001176

REPLACED BY
ART 34 AMDT

30

CLAIMS

1. A method of producing biogas by anaerobic diges-
5 tion of organic matter, characterised by
grinding organic matter,
mixing the organic matter with a liquid to form a
slurry with a dry solids content of 15-45% by weight TS,
feeding the slurry to a tank reactor (2; 102; 202;
10 302) and, in the tank reactor, contacting the slurry with
biogas-producing bacteria for digestion under anaerobic
conditions, and
digesting the slurry in the tank reactor (2, 102;
202; 302) at a dry solids content of 5-10% by weight TS
15 while producing biogas.
2. A method as claimed in claim 1, in which the
ground organic matter is mixed with a liquid to form a
slurry with a dry solids content of 20-40% by weight TS.
3. A method as claimed in claim 1 or 2, in which at
20 least half of the total dry solids of the slurry origi-
nates from grain and/or dried grain offal and/or mixtures
thereof.
4. A method as claimed in claim 3, in which the
grain is essentially present in the form of whole and
25 screened grains.
5. A method as claimed in any one of the preceding
claims, in which organic matter of a type other than the
first-mentioned organic matter is also digested in the
reactor (202; 302), at least 10% by weight of the total
30 dry solids introduced into the reactor originating from
grain and/or dried grain offal included in the first-
mentioned organic matter.
6. A method as claimed in any one of the preceding
claims, in which the liquid with which the organic matter
35 is mixed is essentially pure water.
7. A method as claimed in any one of claims 1-5, in
which the liquid with which the organic matter is mixed

WO 2004/016790
REPLACED BY
ART 34 AMDT

CT/SE2003/001176

31

at least partly is digested sludge which is removed from the reactor (2; 102; 202; 302).

8. A method as claimed in any one of the preceding claims, in which the organic matter is dried to a dry solids content of at least 70% by weight TS before being ground.

9. A device for producing biogas by anaerobic digestion of organic matter, characterised in that the device (1; 100; 200; 300) comprises a premixing tank (18; 118; 218; 318) for mixing ground organic matter with a liquid to a slurry with a dry solids content of 15-45% by weight TS and a feed pipe (26, 4; 126, 104; 204; 304) for feeding the slurry to a sealable, essentially gas-tight tank reactor (2; 102; 202; 302) for digesting the slurry at a dry solids content in the tank reactor (2; 102; 202; 302) of 5-10% by weight TS, said tank reactor (2; 102; 202; 302) having an inlet (4; 104; 204; 304) for slurry from the premixing tank (18; 118; 218; 318) and outlets (6, 8; 106, 108; 206, 208; 306, 308) for produced biogas and formed digested sludge.

10. A device as claimed in claim 9, in which a mill (14; 114; 214; 314) is arranged for grinding the organic matter before being introduced into the premixing tank (18; 118; 218; 318).

11. A device as claimed in claim 9 or 10, in which a supply pipe (122; 222) is arranged for feeding digested sludge from the reactor (102; 202) to the premixing tank (118; 218).